

PVC SHRINKABLE LABEL MAKING MACHINE

- GLUE SEALING MACHINE
ACSF-30G SERIES



- PVC RE-REELING & SEALING
QUALITY INSPECTING MACHINE
REF-Q30 SERIES



- SMALL LABEL CUTTING MACHINE
ACDV-30S SERIES



ACSF-30G SERIES

Materials

- Shrinkable films , e.g. PVC and PET films

Tube Making

- The automatic glue-flow controller can determine the most appropriate amount of glue according to the speed machine and apply it without the need for manual adjustment.
- The finish -roll can be put on cutting machine (ACDV-30S) to be cut into pieces of labels.

Optional Accessories

- Pneumatic loading device (in unwind section)
- Unwind 3" airshaft
- Edge position control (EPC)
- Stroboscope with photo sensor
- Automatic unwind tension controller

- Roller sealing device
- Automatic rewind tension control system
- Paper core rewind device
- Small size tube forming device for tube width 15-30 mm (size as request)
- Roller type center sealing device. Model: ACSF-30GR

	Net weight	Area required
ACSF-30G	800kg	L 6798 x W 4441 x H 1552 (mm)
Max. parent web width	610 mm	
Max. parent web diameter	500 mm	
Max. tube width	30~300 mm	
Max. rewind diameter	800 mm	
Max. machine speed	200 M/min.	

REF-Q30 SERIES

Materials

- PVC shrinkable label tube

Inspecting Section

- Gun-type air injecting device makes inserting the air to sealing tube easily.
- Equipped with Synchronizing stroboscope with photo sensor, provides high efficiency and reliable printing quality inspection.
- Automatic sealing quality inspection system. (Machine stops when sealing defect)

Optional Accessories

- Perforating device (continuously in film moving direction)
- Film reversible running function

	Net weight	Area required
REF-Q30	600kg	L 3800 x W 2100 x H 1400 (mm)
Max. parent web width	300 mm	
Max. parent web diameter	600 mm	
Unwind/rewind core inner diameter	3" & 6"	
Max. machine speed for printing inspection	200 M/min.	
Max. machine speed for sealing inspection	80 M/min.	

ACDV-30S SERIES

Materials

- Paper, plastic films

Perforation

- Here are two types of perforators installed in this machine: Circular type and straight type, which can perforate the label vertically and horizontally at the same time.

Cutting Section

- Equipped with servo motor and driver, the machine can speed up to 400 cuts/min (as the cutting length is less than 50mm), and raise the accuracy of cutting length.
- Equipped with photo sensor (German made), provide accurate cutting position control.

Optional Accessories

- Paper core unwind device
- Automatic unwind tension controller
- Sealing station (Model: ACDV-30S)
- Conveyer
- Lug cutter (lug in front & cavity in back, or lug in front & straight in back)

	Net weight	Area required
ACDV-30S	600kg	L 2395 x W 1066 x H 1415 (mm)
Max. unwinding width	300 mm	
Max. unwinding diameter	700 mm	
Max. cutting length	400 mm (plain film) 300 mm (printed film)	
Max. machine speed	400 Cuts/min.	